



PROBE CURRENT METER

- **DIRECT READOUT OF ABSORBED CURRENT**
- **3½ DIGIT RESOLUTION**
- **LOW COST**

A low cost 3½-digit liquid crystal display readout of Electron Beam Probe Current. The free standing meter is battery powered and measures from below 1pA to 2µA in 5 switched ranges.

The meter has automatic zero correction but there may be small residual error not exceeding 5pA at 25°C. Where absolute readings are required on low ranges this small error may be subtracted from the reading obtained.

The input is designed to accept large overloads in excess of 100µA without sustaining damage.

Its small size allows the unit to be easily located near the SEM itself.

A Faraday Cup is supplied with each unit to enable accurate measurements of probe current to be made. If an appropriate feedthrough from the SEM chamber is not available, K.E.Developments can usually supply a suitable one but at an additional cost.



SPECIFICATIONS

Ranges.

1.99.9pA accuracy +/- 5% f.s.
1.999nA accuracy +/- 5% f.s.
19.99nA accuracy +/- 2% f.s.
199.9nA accuracy +/- 2% f.s.
1.999µA accuracy +/- 2% f.s.

Auto Zero Correction. Max error 5pA at 25°C

Overload. In excess of 100µA

Power. Battery 4 x AA alkaline cells giving typically 10,000 hours operation (1.2 years).

Size. 130mm(W) x 70mm(H) x 115mm(D)

Warranty Period. Two years from date of purchase.



K.E.DEVELOPMENTS LIMITED

The Mount, Toft, Cambridge, CB3 7RL, England
Telephone +44 1223 263532 Fax +44 1223 263948
Web Site. WWW.KEDEV.CO.UK - Email. sem@kedev.com

